

## Codification of Spare Sleeves for Air operated Pinch Valves

Example Code-No.:

<b>M</b>	<b>025.</b>	<b>02X</b>	<b>K</b>	<b>FFLM</b>	<b>040.</b>	<b>03</b>
<b>1</b>	<b>2</b>	<b>3</b>	<b>4</b>	<b>1</b>	<b>2</b>	<b>3</b>

- 1. Type:**
- M** - Sleeves
  - FFLM** - Flange sleeves for VF series, DN40-100
  - FLM** - Flange sleeves for VF series, DN125-200, as well as for old valves models type V

**2. Diameter:** in mm

- 3. Sleeve quality:**
- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li><b>01X</b> = CR (neoprene)</li> <li><b>02X</b> = NR (natural rubber) food quality</li> <li><b>02LS</b> = NR food black</li> <li><b>03X</b> = NR anti-abrasive</li> <li><b>03LF</b> = NR conductive</li> <li><b>03H</b> = NR high temp.</li> <li><b>04HTEC</b> = EPDM / EPDM food black</li> <li><b>04HTECLF</b> = EPDM conductive / EPDM food black conductive</li> </ul> | <ul style="list-style-type: none"> <li><b>04LW</b> = EPDM foodpale</li> <li><b>05</b> = FPM / FKM (viton)</li> <li><b>06</b> = Silicone</li> <li><b>07X</b> = NBR (nitrile)</li> <li><b>07LS</b> = NBR foodblack</li> <li><b>07LW</b> = NBR foodpale</li> <li><b>07LF</b> = NBR conductive</li> <li><b>08X</b> = CSM (hypalon)</li> <li><b>09X</b> = IIR (butyle)</li> </ul> |
|--|--|

**Flange sleeves (FLM/FFLM) do not include an „X“, (e.g. 01, 03)**

Variations with appendix LF (e.g. 03LF) are standing for conductive sleeves (< 10<sup>6</sup> Ohm).  
 Variations with appendix SF (e.g. 03SF) are standing for silicone-free sleeves.  
 Combinations available (e.g. ....03SFLF).

- 4. Sleeves for air operated pinch valves of VMC / VMP series in nominal sizes DN10-25 are additionally marked with a K (=short length) → e.g. M020.04K**

Technical details subject to change without notice.



**Basecamp Process Components, LLC**

8055-C Corporate Blvd., Plain City, Ohio 43064, USA

T: +1 614-873-8995 • E-mail: [info@akopinvalves.com](mailto:info@akopinvalves.com) • Web: [www.akopinvalves.com](http://www.akopinvalves.com)